### **SOLAR** Pro.

## Three solenoid valves on the excavator energy storage device

What is a hydraulic excavator energy saving system?

In order to address these issues, a hydraulic excavator energy saving system based on a three-chamber accumulatoris proposed. Firstly, the conventional piston-type hydraulic accumulator is integrated with the hydraulic cylinder to form a three-chamber accumulator, which has a pressurizing function during energy storage.

Can intelligent control strategies improve the control precision of excavator energy saving systems? Additionally, there is potential for research in developing intelligent control strategies for the TCA-based energy saving system, aiming to elevate the control precision of excavator energy saving systems to a higher level. Cheng Yang: Methodology, Formal analysis, Writing - original draft.

How intelligent hydraulic excavator control system based on PID method?

Design of Intelligent Hydraulic Excavator Control System Based on PID Method Abstract. Most of the domestic designed hydraulic excavators adopt the stant power design method and set 85%~90% of engine power as the hydraulic system adoption power, it causes high energy loss due to mismatching of between the engine and the pump.

Can a hydraulic excavator save energy?

Then, a hydraulic excavator energy saving system based on three-chamber accumulator is proposed, which can store and reuse the energy loss from throttling and overflow of the hydraulic system without changing the hydraulic system of the excavator.

What is the difference between electronic control system and excavator?

Based on research with colleges and universities, domestic company has core technology on fault monitor system in excavator, while electronic control has a certain gap between domestic and foreign company. So, there is still and economic value for researching on electronic control system and energy for excavator.

Can a three-chamber accumulator save energy in excavator boom?

This study introduces a novel energy saving system for recovering and reusing the potential energy of excavator boom. The system is based on three-chamber accumulator (TCA) and offers high energy recovery efficiencywhile maintaining excellent boom speed control performance.

In an excavator, the solenoid on a hydraulic pump serves as a control valve for regulating the flow of hydraulic fluid. The primary function of the solenoid is to control the activation or deactivation of the pump"s hydraulic ...

The utility model provides a kind of hydraulic crawler excavator accumulator Energy release control device, comprise solenoid-operated proportional control valve, electromagnetic valve, pilot handle, swing arm energy

### **SOLAR** Pro.

# Three solenoid valves on the excavator energy storage device

storage oil cylinder, described solenoid-operated proportional control valve is connected with accumulator on the one hand, be connected with main valve on the ...

Described solenoid-operated proportional control valve comprises valve piece, spool, described spool is arranged on valve piece inside, at the arranged outside spring of spool, in the inner side of spool, gear groove is set, in the time that accumulator is carried mixed oil and gas to swing arm energy storage oil cylinder, electromagnetic valve is adjusted the gear groove of spool and the ...

The solenoid valves on an excavator serve a crucial role in the machine's operation. They are responsible for controlling the flow of hydraulic fluid within the system, which in turn affects various functions of the excavator. ... and ...

A rotatory energy recycling control device for a hydraulic excavator, comprising: an oil line selector valve (1), a direction selector valve (2), a sequencing valve (3), a one-way valve (4) and an overflow valve (5); two oil inlets of the oil line selector valve (1) are respectively connected to an opening A and an opening B of a rotary motor; an oil outlet of the oil line selector valve (1 ...

Solenoid valves are electrically operated open or closed valves. These valves control the flow of air, gas or liquids as component of a product or equipment. Solenoid valves operate as normally closed or normally open. In their simplest ...

The utility model discloses an excavator slewing system based on the energy recovery of an energy accumulator and belongs to the technical field of mechanics-electronics-hydraulics integrated control. The excavator slewing system comprises a variable pump, electromagnetic directional valves, check valves, a hydraulic energy accumulator, a slewing motor, a pressure ...

The invention discloses a single-pump excavator energy-saving device based on four-way hydraulic transformer hydraulic energy recovery, which includes a four-way hydraulic transformer connected to the hydraulic system of the excavator, an accumulator, a normally open solenoid valve, a normally closed solenoid valve and A controller, and forms a working oil port, a ...

Taking hydraulic excavator as an example, during each working cycle, the working device is lifted up and lowered down once, the wasted potential energy accounts for 15% of the entire machine output energy [1], [2], [3]. Therefore, to fully recover this part of energy is very significant for improving energy efficiency of the engineering ...

Nowadays, it is restricted for the hydraulic exca-vator to recover and reuse the potential energy of the boom due to the energy storage elements and meth-ods. Therefore, ...

These valves have four ports and are used to control the direction of hydraulic fluid in double-acting hydraulic

## SOLAR PRO. Three solenoid valves on the excavator energy storage device

cylinders or to control the speed and direction of hydraulic motors. Solenoid Valves. Solenoid-actuated directional ...

adjusting valve, three working solenoid valve (pressure up, travel high speed and pilot valve). The electronic energy saving control system was constructed with CAN bus PLC and LCD monitor and was coded with CODESYS software. The control system was consisted of engine control module, pump power adjusted module, engine idle module

The invention discloses a kind of hydraulic crawler excavator accumulator Energy release control device, comprise proportional control solenoid valve, electromagnetic valve, pilot...

For excavator working device trajectory planning ... planned trajectory unusable and directly causes damage to key components such as hydraulic cylinders and proportional valves in robotic excavators. Alternatively, merging time terms can result in extremely long operation times when aiming for minimal impact or energy consumption, which is ...

As the boom of a hydraulic excavator drops, the potential energy accumulated during the lifting process is converted into thermal energy and dissipated through the throttling action of the hydraulic valve, leading to excessive fuel consumption and serious energy waste. In order to address these issues, a hydraulic excavator energy saving system based on a three ...

Study with Quizlet and memorize flashcards containing terms like valves are mechanical devices designed to control the flow of fluids., a solenoid valve is a combination of three basic units, the armature is also known as plunger and more.

adjusting valve, three working solenoid valve (pressure up, travel high speed and pilot valve). The electronic energy saving control system was constructed with CAN bus PLC

Other valves have solenoid coils and thus allow the oil to flow through them (5,6,9). ... hydraulic motor and used as a temporary energy storage device to prolong the energy conversion time, which ...

Then, the four-chamber cylinder system with three solenoid valves is designed to substitute for the traditional two-chamber boom cylinder in a 6-ton excavator. A valve switching logic, as well as a feedforward and feedback compound speed controller, are presented.

When I was trying to find the problem I found only 1 relief valve on the swing motor and what the kobelco parts manual calls a valve assy reduction which I did take apart and it looked ok and also this is the part where the two pilot lines attach to the motor, one comes from the main spool and one comes from a bank of three solenoid valves attached to the fuel tank, I ...

## SOLAR Pro.

## Three solenoid valves on the excavator energy storage device

The core component is the PRB valve block, which is connected in parallel to the existing main control valve and consists of two slices of the new control valve series from Bosch Rexroth ...

Studies on a 20-ton hydraulic excavator show that the energy that can be potentially regenerated during one duty cycle from the boom, arm, bucket, and swing is as high as 260.4 kJ [3]. For a typical excavator truck-loading cycle, research shows that without energy regeneration the overall efficiency of the centralized system is as low as 22.5% [4].

An energy storage device used in a HE is essentially a temporary energy storage device and should be capable of absorbing and output energy frequently. Assuming that a HE has a design working life of 6000 h and the working period is 20 s [ 90 ] for the digging and dumping cycle, the number of operations for an ERS is N y =6000&#215;60&#215;60/20=1.08&#215; ...

Then, the four-chamber cylinder system with three solenoid valves is designed to substitute for the traditional two-chamber boom cylinder in a 6-ton excavator. A valve switching ...

The invention discloses a kind of hydraulic crawler excavator accumulator Energy release control device, comprise proportional control solenoid valve, electromagnetic valve, pilot handle, swing arm energy storage oil cylinder, described proportional control solenoid valve is connected with accumulator on the one hand, be connected with main valve on the other hand, described pilot ...

The invention discloses one kind based on the recoverable single pump excavator energy saver of four-way hydraulic transformer liquid, including four-way hydraulic transformer, accumulator, normally open solenoid valve, normally closed solenoid valve and the controller in access excavator hydraulic system, and form actuator port, pressure oil port and oil return ...

The main consequences of low-energy efficiency are two-fold. Many tons of carbon dioxide (CO 2) and pollutants of concern are released into the atmosphere, such as nitrogen oxides (NO x), fine particulate matter (PM 2.5), carbon monoxide (CO), and hydrocarbon (HC).Significant examples are the 2,700 tons of annual equivalent CO 2 for a single shovel [2] ...

With reference to accompanying drawing 1-2, a kind of hydraulic crawler excavator accumulator Energy release control device, comprises solenoid-operated proportional control valve 8,...

Figure 4: Solenoid valve locations of SK130& 140 excavators. SK130 and SK140 have a total of 7 solenoid valves. The two solenoid valves SV-3 and SV-4 in the picture above are interchangeable and the three proportional solenoid valves ...

a flywheel is the most common energy storage device. This paper is organized as follows. An excavator movable arm energy-saving device based on a spring group and a reducing roller and a working method are

### **SOLAR** PRO.

# Three solenoid valves on the excavator energy storage device

suitable for an excavator. The potential energy storage device is connected with a movable arm,

The control loop and TCA control valve assembly are integrated on the control valve block, while the energy-saving device is connected to the rodless and rod chambers of ...

In order to improve excavator energy efficiency, an electric excavator scheme using a hydraulic-electric dual-power drive boom system is proposed. A linear actuator, including electro-mechanical unit and hydraulic unit, was adopted in the boom system. The boom velocity is controlled by the electro-mechanical unit instead of hydraulic valve to ...

Web: https://eastcoastpower.co.za

